



















AURORE D60 Fixed canon version

Range	Highly flexible cardanic downlight for integration in a chandelier
Description	Low luminance LED ENGINE 600 to 1.500 lm Rotation 360° - Adjustable tilt 30° + 30° Black finish (other upon request)
Net weight	0.40 kg
Installation	Installation diameter: 67mm No specific tolls required
LED characteristics	2700K - 3000K - 4000K (3500K - 5000K upon request) MacAdam ellipse: 3 SDCM (standard version) - 2 SDCM (premium version) CRI: 90 (standard version) - CRI: 95, R9 > 90 (premium version) UGR < 15
Optical beam	7° - 12° - 15° - 25° - 30° - Elliptic – Special filter, honey comb Upon request
Separate power supply	350mA to 1400mA constant current driver according to selected version Dimmable driver as an option
LED power	6W to 25W driver included
Connection	Supplied with 1m cable
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in.

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.

Wuss

Last update: 14/03/2019

Firalux & LOuss brands

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z Tel.: +33 380 48 65 68 contact@louss.fr www.louss.fr Best group Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE