















V25 PATELLA

Range	LED spotlight for accent lighting		
Description	Black matt finish (except magnet) 3 possibilities of fixing devices: • Tube 10mm high (Patella version), • Tube 10mm high + round metal plate (On Plate version), • Tube 10mm high + magnet (Magnetic version) Rotation: 120° - Tilt: 105°		
Dimensions	Length : 37mm Diameter : 25mm		
Net weight	0.050 kg		
LED characteristics	1 LED : 2200K - 2700K – 3000K – 3500K - 4000K (other upon request) CRI 90 - 95 R9>80 Filter, honeycomb grid upon request		
Optical beam	LED CRI 92 LED CRI 95	10°- 12°- 18°- 24°- 36°- 40°- 54° - 60° - Elliptical Caution: The luminous border is poorly defined with 10° and 12° optics 15°- 17°- 25°- 31°- 36°- 40°- 57° - Elliptical	
Connection	Supplied with 0.5m cable (other length upon request) Individual or series connection to remote constant current driver		
Separate power supply	900mA max constant current driver Dimmable driver upon request		
LED power	2.7W at 900mA max		
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.		
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in. he connections have to be made before powering up.		

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.


lOuss


Last update : 01/08/2024

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z Tel. : +33 380 48 65 68 contact@louss.fr www.louss.fr Best group Firalux & LOuss brands

Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE







V30 PATELLA

Range	LED spot		
Description	Body in black or natural anodised aluminium Special version Mirror Finish		
Dimensions	Head length: 30.90mm - diameter: 30mm Rod length: 19mm		
Weight	0.039 kg		
LED characteristics	1 LED : 2200K - 2700K – 3000K – 3500K - 4000K (other LED colours upon request)		
Optical beam	10° - 12° - 15° - 28° - 32° - 40° (other optical beam upon request)		
Connection	Delivered with 20cm cable (more length upon request) Individual connection or connection in series on external constant current driver		
Separate power supply	350mA – 500mA – 700mA		
LED power	350mA: 1.2W 500mA: 1.8W 700mA: 2.4W (low luminance version)		
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.		
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature 3-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in.		

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.

lOuss

Last update: 20/09/2018

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z Tel. : +33 380 48 65 68 contact@louss.fr www.louss.fr Best group Firalux & LOuss brands

Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE