







ANELO 60

The outdoor floodlight which thrives indoor



















			_	_		_	
	NI	_		$\overline{}$		\sim	\frown
Δ							
-	-	_		_	/ /		•

Range	Surface mounted architectural floodlighting				
Description	Body in natural anodised aluminium (other finishing upon request) Transparent polycarbonate protector, treated to withstand UV Stainless steel bracket				
External diameter	60mm				
Net Weight	0.30 kg				
LED characteristics	1 LED: 2200K - 2700K - 3000K - 4000K - 5000K - 6500K (other LED colours upon request) 1 LED 4in1 RGBW				
Optical beam	Monochrome, twin white: 4° - 6° - 15° - 35° (other optical beams upon request) LED 4in1: 7° - 12° - 24° - 32° - 10x40 elliptical				
Connection	Delivered with 1m standard cable (more length upon request) Individual connection or connection in series on external constant current driver				
Separate power supply	350mA – 500mA – 700mA				
LED power	350mA: 1.2W 500mA: 1.8W 700mA: 2.4W				
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.				
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in.				

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.

Wuss

Last update: 01/02/2019

Firalux & LOuss brands