



## **AURORE D60**

Cylindrical wallmounted version






25º














## **AURORE D60**

## Cylindrical Wall-mounted version

Range	Highly flexible recessed ceiling downlight for general & accent cardanic lighting
Description	Low luminance LED ENGINE 600 to 2.000 lm selected version 13W or 20W Rotation 360° - Adjustable tilt 90° White finish RAL 9003 (other upon request)
Net weight	0.8 kg
Installation	No specific tools required
LED characteristics	2700K - 3000K - 3500K - 4000K - 5000K MacAdam ellipse: 3 SDCM (standard version) - 2 SDCM (premium version) CRI 90 (standard version) - CRI 95, R9 > 90 (premium version) UGR < 15
Optical beam	7° - 12° - 15° - 25° - 30° - 40° - Elliptic - Special filter upon request
Connection	Connectors in the box
Separate power supply	350mA to 1400mA constant current driver according to selected version Dimmable driver as an option
LED power	6W to 25W driver included
Use limitations	The product must be installed into a ventilated area.  Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees.  The drivers, if not delivered by LOuss, must be approved before use.
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty.  The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product.  All products are electrically tested and received a functional burn-in.

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.

**W**uss

Last update: 10/05/2021

Firalux & LOuss brands