





MAGMATO 95

The recessed architectural floodlight Medium Trio
























MAGMATO 95

Range	Recessed architectural floodlighting		
	Body in aluminium		
Description	Head in stainless steel with armoured glass		
	Dedicated recessed box		
External diameter	95 mm		
Net Weight	0.5 kg		
	LED characteristics	Optical beam	Power consumption
4en1 1 LED version	2200K - 2700K - 3000K - 4000K - 5000K - 6500K - Twin White - RGBW (other LED colours upon request) 600 to 800Lm at 700mA	Very high-performance 6° - 10° - 15° - 25° - 35° 6°x32° elliptic	350mA: 3.6W 500mA: 5.4W 700mA: 7.2W
3 LED version	2200K - 2700K - 3000K - 4000K - 5000K - 6500K - Twin White - RGBW (other LED colours upon request) 500 to 600Lm at 700mA	14° - 25° - 30° - 40° - 60° 18°x36° elliptic	350mA: 3.6W 500mA: 5.4W 700mA: 7.2W
Connection	Delivered with 1m standard cable (more length upon request) Connection in series on external constant current driver		
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.		
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in.		

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.

Wuss

Last update: 13/10/2022

Firalux & LOuss brands