









Threaded rod M10x1 + fixing nut







AURORE D40

Pivot version

Range	Highly flexible low luminance spotlight for general & accent lighting
Description	Rotation 360° - Adjustable tilt 30° + 30° White matt finish RAL 9003 (other upon request)
Net weight	0.150 kg
Installation	Fixation through threaded rod M10x1 + nut
LED characteristics & Luminous efficiency	2700K - 3000K - 3500K - 4000K - 5000K MacAdam ellispe : 3 SDCM CRI90 (standard version) - CRI 95, R9 > 80 UGR < 15 300 to 800Im according to selected version (3W to 8W)
Optical beam	6° - 10° - 15° - 20° - 25° - 30° - 35° - 40° - 55° - 60° - Elliptic Special filters, honey comb grid upon request
LED power	3W to 8W
Separate power supply	350mA to 700mA constant current driver according to selected version Dimmable driver upon request
Connection	Supplied with 0.50m cable
Use limitations	The product must be installed into a ventilated area. Any use with an ambient temperature higher than the specified ambient temperature (Ta) would lead to a more rapid mortality of the product and the withdrawal of our guarantees. The drivers, if not delivered by LOuss, must be approved before use.
Warranty	Life span: L80B10 at 50,000 hours (80% remaining flux) at 25°C ambient temperature. 3-year parts and labour warranty. The warranty does not apply to products that have been opened, modified or repaired and does not cover the effects of a wrong connection, careless, abusive handling, overvoltage, lighting injury, as well as the normal wear of the product. All products are electrically tested and received a functional burn-in.

All the connections have to be made before powering up, otherwise the luminaires could be seriously damaged.

lOuss

Last update : 31/01/2022

Firalux & LOuss brands

SARL, Capital 40 000€ RCS DIJON B 503 367 245 TVA/VAT n°: FR24 503 367 245 APE 4676Z Tel. : +33 380 48 65 68 contact@louss.fr www.louss.fr Best group Siège social / Head Office PA Les Terres d'Or Route de Saint Philibert 21220 Gevrey Chambertin - FRANCE